

## Biolight V6 Vital Signs Patient Monitor – New



Stock Photo – Options May Vary

The Biolight V6 Vital Signs Patient Monitor Features: NIBP, Pulse Rate, and SpO2. It also has a 7" Color Anti-Glare TFT LCD with a Pixel Resolution of 234 x 480.

Power Supply: Input Voltage; AC 100V - 240V and comes with a Lithium Ion Battery that allows approximately 8 Hours usage. Measurement Range is 20 - 250 bpm.

Optional: Patient Monitor Wall and Mobile Stands, Printer, and Infrared Temperature are available.

Manufacturer Warranty: 2 Years, 90 Days for Accessories

- NIBP
- Pulse Rate
- SpO2
- Lithium Battery Included
- Battery Usage Time: Approx. 8 Hours
- 7" Color Anti-Glare TFT LCD Screen
- Light Weight: Approximately 5.5 lbs.
- Powerful Storage Capacity
- Printer (Optional)

### Specifications:

- Biolight Digital SpO2 Measurement Range: (0 - 100)%
- Resolution: 1%
- Weight 2.5kg (approximately 5.5 lbs)
- Battery Type: Lithium Ion
- Operating Time: Approx. 8 Hours
- Charge Time: 6h to 100%
- Power Supply, Input Voltage: AC 100V - 240B
- Patient Quantity: 1000
- Recording Number: 16000
- Alarm Events: 1000
- PR Measurement Range: 20 - 250 bpm

*\*\*Brochure and images are a general overview of the product. Actual product options may vary.*