

# Then Choose your platform.



**9005BPSTO**  
with Optional  
Desktop Caddy

## Desktop

The ADView 2 features a modern, compact design that's self-standing for desktop or tabletop use.

A built-in handle offers instant portability, while the optional caddy helps keep accessories organized.



**9005BPSTO**  
with Optional  
Wall Mount



## Wall Mount

With our custom mounting plate, the ADView 2 can be easily mounted to the wall or an Adstation EENT system.



**9005W**  
Basket with  
Wall Mount

## Mobile

With our rugged, easy to assemble, five-legged mobile stand, you can move the instrument from room to room for optimum workflow. The stand comes with an oversized basket to keep accessories organized. Mounts for optional printer and scanner hardware are also available.



**9005BPSTO**  
with Optional  
Mobile Stand  
(9005M)



## Ordering Information

### ADView® 2 Diagnostic Station

ADView 2 BP	9005BP
ADView 2 BP/Temp	9005BPTO
ADView 2 BP/SpO <sub>2</sub>	9005BPS
ADView 2 BP/SpO <sub>2</sub> /Temp	9005BPSTO

For configurations with Masimo SET replace the S suffix with SM (e.g., 9005BPSM)

#### BP base unit includes:

Rechargeable lithium-ion battery; U.S. power cord; 10-foot length of tubing; Adult Plus and Large Adult Plus cuffs; Mini USB to USB Cable; Quick Reference Guide; Quickstart Guide.

#### Temperature module includes:

Oral/axillary probe and well (blue) and box of 20 probe covers.

#### SpO<sub>2</sub> ChipOx module includes:

Adult finger sensor and 8-foot extension cable.

### ADView® 2 Mounting Platforms

Desktop Caddy*	9005D
Wall Mount with Basket	9005W
Mobile Stand with Basket	9005M
Printer Shelf for Mobile Stand	9005PSHELF

\*Base unit is self-standing. Add the optional Desk Caddy to keep cuffs and cords organized.

### ADView® 2 Modules

(When Sold Separately)

Temperature Module, Oral/Axillary	9005TO
Temperature Module, Rectal	9005TR
SpO <sub>2</sub> ChipOx Module	9005S
SpO <sub>2</sub> Masimo Module	9005SM

### Technical Specifications

Dimensions, Base Unit	8" x 6.75" x 5.2"
Weight, Base Unit	0.6 lbs (284 g)
BP Range: Adult	Dia: 20-200 mmHg / Sys: 40-260 mmHg
BP Range: Pediatric	Dia: 20-160 mmHg / Sys: 40-230 mmHg
BP Accuracy	Meets or exceeds ANSI/AAMI/ISO 81060-2:2013 for non-invasive accuracy (±5 mmHg mean error with 8 mmHg SD)
Heart Rate Range	30-220 BPM
Temperature Range	86.2°F to 109.2°F (30.1°C to 42.9°C)
Quick Temp Mode	Response: 3-6 sec; Accuracy ±0.5°F (±0.3°C)
Standard Temp Mode	Response: 6-14 sec; Accuracy ±0.2°F (±0.1°C)
Direct Temp Mode	Response: 60-120 sec; Accuracy ±0.2°F (±0.1°C)
SpO <sub>2</sub> Saturation (Normal)	ChipOx/Masimo: 70-100% Arms ±2%

### Warranty

Main Unit, SpO <sub>2</sub> modules, temp module	3 Years
Blood Pressure Cuffs	2 Years
Desktop Caddy, Wall Mount, Mobile Stand	2 Years
Accessories (SpO <sub>2</sub> Sensors, temp probes, etc.)	90 Days

Additional specifications online at [www.adctoday.com/adview2](http://www.adctoday.com/adview2)

Distributor

### ADView® 2 Cuff Options

Adult, Navy	9005-11AN-1MB
Adult Plus, Navy	9005-11APN-1MB
Child, Green	9005-9CGR-1MB
Small Adult, Royal Blue	9005-10SARB-1MB
Large Adult, Burgundy	9005-12XBD-1MB
Large Adult Plus, Burgundy	9005-12XPBD-1MB
Thigh, Brown	9005-13TBR-1MB
Pediatric Cuff Kit (Child, Small Adult, Adult)	9005CKP
Adult Cuff Kit (Adult, Large Adult)	9005CKA
Five Cuff Kit (Child, Small Adult, Adult, Large Adult, Thigh)	9005CK

All cuffs equipped with male bayonet connector.

Cuff Colors and Limb Ranges:			
Child 12-19 cm	Small Adult 17-25 cm	Adult 23-33 cm	Adult Plus 28-40 cm
Lg. Adult 31-40 cm	Lg. Adult Plus 40-55 cm	Thigh 38-50 cm	

### ADView® 2 Accessories

SpO <sub>2</sub> ChipOx Finger Sensor, Adult	9005SP
SpO <sub>2</sub> ChipOx Finger Sensor, Pediatric	9005SPDYS
Thermometer Probe Covers (20/Box, 25 Boxes/Case)	9000TP
Thermometer Probe Covers (5000/Case)	9000TP-5000
Oral/Axillary Temperature Probe	9000TOP
Oral/Axillary Temperature Well	9005TWB
Oral/Axillary Temperature Kit (Probe, Well, Probe Covers)	9005TOK
Rectal Temperature Probe	9000TRP
Rectal Temperature Well	9005TWR
Rectal Thermometer Kit (Probe, Well, Probe Covers)	9005TRK
Rechargeable Lithium-Ion Battery	9005BAT
Power Cord, U.S., 120VAC	9005PC
Power Cord, Euro, 240VAC	9000PCEU
Power Cord, U.K., 240VAC	9000PCUK
Power Cord, Australia 120VAC	9000PCAU
USB Wi-Fi Dongle	9005DON
Printer with Paper	9005P
Barcode Scanner	9005SCAN



American Diagnostic Corporation  
55 Commerce Drive  
Hauppauge, NY 11788  
tel: 631-273-9600  
toll free: 1-800-232-2670  
fax: 631-273-9659  
[www.adctoday.com/adview2](http://www.adctoday.com/adview2)  
info@adctoday.com

Components made for ADC® by:  
SunTech Medical, Inc.  
507 Airport Boulevard  
Suite 117  
Morrisville, NC 27560-8200

SunTech Medical Ltd.  
Oakfield Industrial Estate  
Eynsham, Oxfordshire  
OX29 4TS UK



© 2016 American Diagnostic Corporation. ADC, the ADC logo, and ADView are registered trademarks of American Diagnostic Corporation. All other trademarks are the property of their respective owners.

ADVIEW2CAT

Printed in U.S.A.

# Introducing the New ADView® 2 Clinical-Grade Diagnostic Station from ADC®

## Modular, Multiplatform, Affordable – Evolved

The first – and still only – truly modular diagnostic station.

Now in its second generation.



Blood Pressure • Temperature  
SpO<sub>2</sub> • Pulse Rate



# First

## Select the configuration you need.

### MODULAR DIAGNOSTIC STATION BASE UNIT

#### It all begins with blood pressure.

The ADView 2 easily captures automated blood pressure measurements at the touch of a button. Our non-invasive blood pressure module uses the oscillometric method, with both pulse rate and the mean arterial blood pressure (MAP\*) displayed in about 30 seconds. With seven available cuff sizes, ranging from child to thigh, the ADView 2 can be used for patients ages three and older. Adult Plus and Large Adult Plus cuffs come standard.

\*MAP not validated for use in the U.S.

#### With a manual mode option for added versatility.

Our original ADView was the first diagnostic station to offer a manual mode (an innovation developed even earlier for our e-sphygm™), allowing you to capture blood pressure with your stethoscope using the traditional auscultatory method without changing cuffs. Manual mode provides important versatility for your patients with arrhythmias or other complex needs.

#### And a new, customizable averaging protocol.

With the ADView 2, we also offer a user-definable averaging mode with programmable options including two to five readings, start and interval delays, and first-measurement exclusion. Averaging is recognized as a key component of accurate blood pressure measurement and was used in the recent SPRINT trial conducted by the National Institute of Health.

### OPTIONAL MODULES AND ACCESSORIES

Our optional modules and accessories allow you to create a diagnostic station perfectly suited to your needs. Add them at the time of purchase and we'll ship your ADView 2 configured. Or add new modules as you need them to upgrade in the field. Our connect-and-go construction makes expanding your ADView 2 effortless!

#### Temperature Module

Add a Covidien Filac™ 3000 Thermometry module to your ADView 2 for an oral or axillary temperature reading in as little as 3-6 seconds. The module features both Fahrenheit and Celsius scales, switchable with the touch of a button, a cold mode for lower ranges, and a built-in, color-coded storage well for the probe and box of 20 disposable probe covers (included). An optional color-coded rectal chamber/probe is also available.

#### Pulse Oximetry Module

Add a pulse oximetry module to your ADView 2 to measure oxygen saturation of arterial blood flow in about 10 seconds. The ChipOx Nellcor™-compatible SpO<sub>2</sub> module displays pulse-rate signal strength during measurement, and comes with a reusable finger clip sensor and 8-foot cable. An optional pediatric/multi-site sensor is also available. Alternatively, choose the Masimo SET® SpO<sub>2</sub> module upgrade.



### STANDARD FEATURES

- Clinical-grade Advantage™ BP technology from SunTech Medical
- Customizable BP averaging
- Manual mode for real-time BP verification
- Pediatric mode for younger patients
- Lithium-ion power for longer-lasting battery life and a lighter weight
- Network enabled with HL7 messaging for electronic data transfer
- Built-in memory with up to 99 charting sessions
- LCD display with simple, easy-to-use design
- LAN/Ethernet and two USB ports

## The Complete ADView® 2 Modular Diagnostic Station

ADC®, a world leader in core diagnostic products for more than 30 years, has once again partnered with SunTech Medical®, the premier developer of innovative blood pressure technology, to create the next generation in modular diagnostics. Our ADView® 2 starts with a blood pressure base unit. From there, optional modules and accessories allow you to create a diagnostic solution perfectly suited to your needs.



Choose options at the time of purchase and we'll ship your ADView 2 configured. Or add new modules as you need them to upgrade in the field.

Our connect-and-go construction makes expanding your ADView 2 effortless!

### ADVANCED FEATURES

**Networking via Ethernet or Wi-Fi** – The ADView 2 is network ready and can be connected through built-in Ethernet (cable not included) or optional Wi-Fi.

**Advanced EMR Connectivity** – The ADView 2 supports the IHE HL7 messaging standards for integration of patient data with your existing electronic medical records (EMR) system. When configured with the optional barcode scanner, you can easily send measurements directly to the EMR. Alternatively, use our ADViewer middleware solution for saving and printing readings on your local network.

### ADDITIONAL ACCESSORIES

**Printer** – An optional thermal printer can be connected to your ADView 2 using one of the unit's two USB ports.

**Barcode Scanner** – An optional barcode scanner, ideal for uploading patient IDs directly to your facility's EMR, can be added to your ADView 2. The scanner connects via USB.