

Bed		

Low position – floor to center of deck	13" (33 cm)*
Low position – floor to edge of deck	17" (43.2 cm)*
High position – floor to center of deck	30" (76.2 cm)**
High position – floor to edge of deck	34" (86.4 cm)**
Maintains low height when placed in chair	Yes
Headboard/push handles maintain same height regardless of patient surface height	Yes

### **Sleep Surface**

Width	35.5" (90.2 cm)
Length, fully extended	86" (218.0 cm)
Length, fully retracted	75" (191.0 cm)
Radiolucent sleep deck	No
Surface weight limit	500 lbs

### **Overall Width**

Siderails stowed	37" (94.0 cm)
Siderails up	40" (102.0 cm)

# **Overall Length**

Fully extended	94.5" (240.0 cm)
Fully retracted	82.5" (210.0 cm)

### **Bed Angles**

Dea Alligies	
Head section	0° to 65°
Knee section	0° to 16°
Foot section	0° to -27°
Max Trend/Reverse Trend	15° / 10°
Head and Trend angle indicators	Yes

## **Caster and Braking System**

Optional IntelliDrive® power transport	Yes
Caster diameter with IntelliDrive® power transport	5" (12.7 cm) 6" (15.2 cm)
Four-wheel braking	Yes
Brakes lock both rolling and swiveling	Yes

## **Optional Light Alerts**

Feature indicators	Low low bed/chair,
	siderails down, brake not
	set hed exit not armed

#### **Optional Bed Exit Alarm System**

Sensitivity levels	3
Modes	Positioning, Exiting, Out-of-Bed, Alarm Silence

#### **Optional Scale System**

Accuracy	1% of patient weight
Weigh in any position (except Trend/Rev Trend)	Yes
Scale weight capacity	500 lbs (227 kg)

## **Patient Weight Limit**

Patient weight, all surfaces	500 lbs (227 kg)
Safe working load, including all accessories	550 lbs (250 kg)

#### **Patient Controls**

Siderail patient bed controls	Standard
Docking pendant	Optional
SideCom® patient communication controls (Nurse call, universal TV/radio, and lighting)	Optional

## **Electrical Characteristics**

Backup battery power	Standard
Standards test to	UL2601 & IEC 60601-1

Hill-Rom reserves the right to make changes without notice in design, specifications and models. The only warranty Hill-Rom makes is the express written warranty extended on the sale or rental of its products. ©2014 Hill-Rom Services, Inc. ALL RIGHTS RESERVED.

**ORDER NUMBER** 178171 rev 3 24-APR-2014 ENG – US

Zinc Number US-AC-1213-0641

www.hill-rom.com

\*Optional IntelliDrive® power transport adds 4" (10.2 cm) height to the bed in its low position



<sup>\*\*</sup>Optional IntelliDrive® power transport adds 1.5" (3.8 cm) height to the bed in its high position