

InTouch[®]

Critical Care Bed



Basic needs. Simplified care. Exceptional outcomes.

The acceptable number of adverse events in your facility is zero. With the right technologies and processes in place, potential adverse events often can be prevented.

Our InTouch bed delivers intuitive, advanced technology and backs it with hospital programs and processes that enable you to minimize the risk of never events while providing a higher quality of care safely, conveniently, and consistently.

All InTouch beds are part of Stryker's Connected Hospital Service which can link via wire or wirelessly to your hospital's choice of information systems.*



iBed Awareness monitors local bed status information, alerting caregivers visually, audibly or remotely if present parameters are compromised.



Our Zoom Drive System is fully integrated and helps to provide mobility and efficiency for both the patient and the caregiver.



Control all bed functions with an easy, intuitive touch screen interface using a powerful on-bed Windows computer.

Intuitive controls are located on all four sides with advanced caregiver controls on the footboard, in an ergonomic BackSmart position, away from the patient's reach and bedside clutter.

One touch electric brakes help to prevent unnecessary bending and stretching required by traditional brakes.

Chaperone Bed Exit System with Zone Control tracks the patient's position and alerts the caregiver of any changes through a local or remote alarm. The caregiver can choose a spoken patient command in place of an alarm.

iBed Awareness monitors local bed status information, alerting changes to preset positions visually, audibly or remotely.

Protocol reminders help organize and improve care efficiencies with hospital best practices.

Spoken language translations help improve communication with Limited English Proficiency (LEP) patients.

On-board sound feature helps to create a soothing background for patients.

Support surfaces can be changed as therapies dictate, and our Isolibrium support surface can be directly controlled by the touch screen.

InTouch Critical Care Bed



Standard features

- Touch screen interface
- Bed history screen
- Smart maintenance screen
- Event manager screen
- Smart scale
- BackSmart pivot in-bed patient positioning
- Chaperone Bed Exit System
- Electric brake with mechanical back-up
- CPR foot pedal and CPR-ready headboard
- Full functionality battery back-up
- Enhanced cardiac chair
- One-handed siderail release
- Siderail-storable patient control pendant
- Radiolucent litter top
- Patient lock-out controls
- Integrated pump holder
- Single 110-volt auxiliary outlet
- LED nightlight
- DC actuators
- USB port
- Three-zone bed exit alarm
- One touch HOB 30-degree button
- Traction equipment socket
- Quick-reference guide
- Foley bag hooks

Specifications

Model number	2131 (2141 Zoom)
Overall length	90" (228.6 cm)
Overall width	
Siderails up	42" (106.7 cm)
Siderails down	40.5" (102.9 cm)
Weight capacity	550 lb. (249 kg)
Height range (to litter top)	
High	33" (83.8 cm)
Low (standard with 6" casters)	16" (40.6 cm)
Litter positioning	
Backrest	0°–70°
Knee gatch	0°–15°
Trend./reverse trend.	±12°
Patient surface	35" x 84" (89 x 213 cm)
Caster diameter	5.5" (14 cm)

Optional features

<ul style="list-style-type: none"> • iBed Awareness • Protocol Reminders • iBed Serial Port • iBed Wireless • Calculator • Converter • Translator • Audio • Documentation • Zoom Motorized Drive System 	<ul style="list-style-type: none"> • Oxygen bottle holders <ul style="list-style-type: none"> • Headboard-mounted • Upright • Dual 110-volt auxiliary outlets • Head end nurse control panel • Bed extender and pad • Pendant clip • Transport tray/patient helper • IV poles • 1 or 2 permanent 	<ul style="list-style-type: none"> • Smart TV • Room light controls • Nurse call • Pillow speaker • X-ray cassette holder • WallSaver Breakaway Wall Connector • Foot end roller bumpers • Line management accessory
---	---	--

Electronics

Agency approvals	UL
Volts	120 VAC
Ampere rating	9.8 A (with optional auxiliary outlets)
Current leakage	< 100 microamperes
Frequency	50/60 Hz
Hospital grade plug	Yes
EMC compatible	Yes

Stryker reserves the right to change specifications without notice.

*With proper third party systems.

3800 E. Centre Avenue
Portage, MI 49002 USA
t: 269 329 2100
toll free: 800 327 0770

patientcare.stryker.com

Stryker Corporation or its divisions or other corporate affiliated entities own, use or have applied for the following trademarks or service marks: BackSmart, Chaperone, Connected Hospital, iBed, InTouch, Isolilibrium, Stryker, Zone Control, Zoom. All other trademarks are trademarks of their respective owners or holder.

Printed in U.S.A.
Mkt Lit-180-27 Apr 2007 Rev G.1
Copyright © 2017 Stryker